MINIBLUE®





3.5-8 KW

PERFORMANCE

)) 21 dba

MAX FLOW	MAX HEAD	MAX LIFT
8 L/ HOUR	8 METRES	5 METRES

Running either wet or dry, the MINIBLUE® is whisper quiet whilst reliably removing condensate and debris. Inherently reliable whilst self priming it gives peristaltic performance at the price of a piston pump. The MINIBLUE® is small enough to quickly fit, or retro fit, into any existing installation, saving both time and money.

SENSING OPTION

MINIBLUE® pump available with:

CR PLUG	TEMPERATURE SENSOR
X87-500	X87-504



All of the BLUEDIAMOND® pumps have the ability to run dry without burning out. Enabling them to remove any liquids, preventing organic growth inside the tubing.




QUIET

Quiet in all stages of operation and not only when set to quiet mode or relying on a soft start setting.


UNIT


PERFORMANCE



DIMENSIONS (MM)


V (VFRTICAL)





H (HORIZONTAL)

DISCHARGE PIPE RUN



• (, = ,)	11 (1.10.1.12.01.1.1.1.1.2)
8 M	0 M
7 M	3 M
6 M	6 M
5 M	9 M
4 M	12 M
3 M	15 M
2 M	18 M
1 M	21 M

The MINIBLUE® can be mounted in any orientation up to 5m away from the A.C unit.

